

Galvanising Bar

MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE

Hazard Classification according to criteria of Worksafe Australia

COMPANY DETAILS



Company: Dynaweld Industrial Supplies Pty Ltd
Address: 123 Fairford Road
Padstow NSW 2211
Australia
Phone: (02) 9772 1144
Fax: (02) 9774 1685
ACN: 076 580 704

IDENTIFICATION

Product Names: Bossweld Galvanising Bar
Other Names:
UN Number: None Allocated
Dangerous Goods Class: None Allocated
And Subsidiary Risk: None Allocated
Hazchem Code: None Allocated
Poisons Schedule Number: None Allocated
Use: Soft Soldering (Repairs)

PHYSICAL DESCRIPTION & PROPERTIES

Appearance: Silver/Grey Solid
Colour: Silver Grey
Odour: Nil

Boiling Point: N/A
Melting Point Range: 183°C
Vapour Pressure: N/A
Vapour Density: N/A
Specific Gravity: 9.6
Flashpoint: N/A
pH: N/A
Flammability Limits: N/A
Solubility in Water: Insoluble

INGREDIENTS

Chemical Name METAL:	CAS Number	Proportion
Tin	7440-31-5	30-37%
Zinc	7440-66-6	7-12%
Lead	7439-92-1	51-63%

HEALTH HAZARD INFORMATION

FIRST AID

Description of necessary measures according to route of exposure

Swallowed: Give plenty of water to drink; seek medical advice if large object has been swallowed

Eye: Irrigate the affected eye(s) with water and seek medical advice to remove the foreign particle if possible

Skin: If molten material comes in contact with the skin and adheres –cool quickly with running water – do not attempt to remove. For metal dust contamination, wash the affected area with soap and water

Inhaled: If fume or dust is inhaled, remove victim to fresh air taking care not to become a casualty. Lay patient down and keep warm and rested. Seek medical attention

Medical Attention and Special Treatment: Treat symptomatically

Aggravated Medical Conditions caused By exposure: Test for lead in blood if patient has had a long term exposure, particularly to dust or fume. Blood lead levels exceeding 100 ug/100ml indicate lead poisoning. Exposure to high levels of airborne or indigested lead may produce symptoms of anaemia, insomnia, weakness, constipation, nausea and abdominal pain. Women of child bearing age should avoid exposure to lead due to post natal effects. Over exposure to Tin and Antimony not expected.

PRECAUTIONS FOR USE

Exposure Standards: Chemical Name METAL:	ES-TWA	ES-STEL	ES-Peak
Tin (Dust & Fumes)	2.0 mg/m ³		
Zinc (Oxide & Fume)	5.0 mg/m ³		

Lead	0.15 mg/m ³
Biological Limit Values	No data available
Engineering Controls:	Adequate ventilation/extraction should be provided to keep exposure to below TWA values and to ensure operator comfort. Vacuuming is recommended
Personal Protection:	An approved dust/fume respirator should be worn when TWA values may be exceeded
Eye:	Safety Glasses or full face mask
Hands/Feet:	Leather gloves, safety boots and protective clothing should be worn and kept clean. Always wash hands before eating, drinking, smoking or using the toilet.
Respiratory Protection:	An approved dust/fume respirator should be worn when TWA values maybe exceeded.
Flammability:	Metal: Non Flammable Resin: Can burn – if enough is extracted

SAFE HANDLING INFORMATION

Storage and Transport:	Material stable. Storage and transport should not present a problem.
Spills and Disposal:	Small Spills/leaks: In molten state allow to solidify and cool. Break up and recycle as scrap
Special Protective Equipment:	Fire fighter should wear self contained breathing apparatus and protective clothing if exposed to products of decomposition.
Addition Information:	Avoid contact with strong acids. Incompatibility: Avoid oxidizing materials, acids and peroxides. Above 500°C lead fumes may be generated.
Large Spills/Leaks:	In molten state allow spill to solidify and cool. Break up and use as scrap.
Fire/Explosion Hazard:	In molten state allow spill to solidify and cool. Break up and use as scrap. Seek advise of supplier. If necessary dam the spill area to prevent entry of molten metal to drains. Scrap solder by-products can be recycled by returning to supplier.
Extinguishing Media:	Dry Chemical Powder or Carbon Dioxide

CONTACT POINT

Andrew Bosco
Director
(02) 9772 1144

The information contained in this MSDS is, to the best of our knowledge correct and complete. This MSDS is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. No warranty express or implied is made to the accuracy reliability or completeness of this document.